
NOTES:
1. FLUID — MIL-H-5606
2. TEMPERATURES — -65°F TO 160°F
3. SYSTEM PRESSURE: OPERATING — 1900 PSI
MIDDLE — 2100 PSI
DEADST — 3120 PSI
4. INTERNAL LEAKAGE — 0
EXTERNAL LEAKAGE — 0
5. EXTERNAL RELIEF VALVE SETTINGS — 1950 PSI
6. WEIGHT (APPROX) — 3.5 POUNDS
HYDRAULIC SCHEMATIC
ITEM NO. | DESCRIPTION
1 FLAP CONTROL VALVE
2 GEAR CONTROL VALVE
3 DOOR CONTROL VALVE
4 SOLENOID
5 CHECK VALVE
6 THERMAL RELIEF VALVE
DETAIL C
APPLIES TO -5 ONLY
SECTION B-B
APPLIES 3 PLACES
SECTION A-A
SEE DETAIL C
SEE SECTION B-B
LANDING GEAR DOWN POSITION
LANDING GEAR UP POSITION
FLAPS UP POSITION
FLAPS OFF POSITION
FLAPS DOWN POSITION
-3 VALVE ASSY SHOWN
-4 VALVE ASSY
-5 VALVE ASSY
REVISED AND REDRAWN
REVISIONS
VALVE ASSY FLAPS AND GEAR
202500