


NOTES:

1. FLUID _____ MIL-H-5600
 2. TEMPERATURE RANGE _____ -65°F TO +160°F
 3. PRESSURES:
 OPERATING _____ 1500 PSI
 PROOF _____ 2250 PSI
 BURST _____ 3750 PSI
 4. BORE _____ 1.116
 5. ROD DIA _____ .673
 6. WEIGHT (EST) _____ 2.5 LB
 7. BREAK OUT FORCE OF RETRACT DIRECTION SHALL NOT EXCEED 15 POUNDS FOR LAST 1.25 TRAVEL
- ⓐ ⓑ INSTALL AN922-4D FITTINGS ON CENTERLINE OF ACTUATOR FACING THE ANCHOR END.

LTR	REVISION DESCRIPTION	DATE	APP
A	26206-5 P1 WAS 26206-2; ADD -2, -3, -4 (REPLACES 26200-1, -5, -6 RESPECTIVELY)	11/3/76	Zly
B	18.00 WAS 17.85 (L. 41) WAS 6.42 (L. 41) WAS 18.19 (L. 28) WAS 12.46 (L. 41) WAS 5.31 (ADD E AND D); ADD (L. 28) (L. 41)	1/3/81	Zly
C	ADD: NOTES: AN922-4D, AN922-4D AND AN92778-4; COMS WAS HMx-56; DELETE WAS 513-6 MS33540-0302	6/9/77	Zly
D	HMx-56 WAS CON-5; DELETE 26228-4 FROM BMM	7/1/77	Zly
E	L. 17.14 WAS 17.85; L. 10.07 WAS 10.07; STL WAS 5.31; 26228-3 WAS 26228-3; JACOBY WAS -2, -3, -4	9/1/77	Zly
F	ADDED -5 ASSY	JCH	10-27-76
G	ADDED -6 ASSY	JCH	10-27-76
H	XAM-5M WAS HMx-56 FOR -2, -3	JCH	10-27-76
J	ADDED -B ASSY	JCH	10-27-76

DASH NO.	A	B	C	D	E
-1	17.00	11.00	5.92	1.40	M535649-04
-2	17.68	11.08	5.92	1.40	M535649-04
-3	12.41	12.48	5.93	1.40	M535649-04
-4	17.50	12.83	6.47	1.20	125-27 NPT
-5	19.04	13.34	5.68	1.40	M535649-04
-6	16.95	11.18	5.77	1.40	M535649-04
-7	17.5	11.58	6.42	1.20	HUDSON
-8	17.0	11.08	5.92	1.20	125-27 NPT

- 1 ACTUATOR ASSY (SHOWN)
- 2 ACTUATOR ASSY
- 3 ACTUATOR ASSY
- 4 ACTUATOR ASSY
- 5 ACTUATOR ASSY (SAME AS -1 EXCEPT AS SHOWN)
- 6 ACTUATOR ASSY (SAME AS -1 EXCEPT AS SHOWN)
- 7 ACTUATOR ASSY (SAME AS -1 EXCEPT AS SHOWN)
- 8 ACTUATOR ASSY (SAME AS -1 EXCEPT AS SHOWN)



ⓐ DETAIL A APPLIES -5 ASSY ONLY

QTY	PART NUMBER	DESCRIPTION	MATERIAL	MATL SPEC	HEAT TREAT	FINISH
1	XAM-5M	ROD END	AURORA	ALT	HMx-56	HEIM
1	26228-3	SPACER				
1	-6	ASSY				
1	MS28778-4	O-RING				
2	AN924-4D	NUT				
2	AN922-4D	FITTING				
1	26202-2	BARREL				
1	AN520-10-2	SCREW (OR EQUIV)				
1	26228-3	SPACER				
1	26206-3	PISTON				
1	26206-5	PISTON				
1	26228-3	SPACER				
1	-5	ASSY				
1	NA5509-6	JAM NUT				
1	HMx-56	ROD END	HEIM			
1	MS28775-212	O-RING				
2	MS28774-212	BACKUP				
1	MS28775-213	O-RING				
1	MS28774-114	BACKUP				
1	MS28775-114	O-RING				
1	MS28774-114	BACKUP				
1	DW1450-3-1	SCRAPER	DOUGE			WASHTON
1	MS2132-5	BEARING				
1	-4	ASSY				
1	-3	ASSY				
1	26206-6	PISTON				
1	26204-1	RETAINER				
1	26202	BARREL				
1	-2	ASSY				
1	-1	ASSY				

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES

DRAWN BY: *hesler* DATE: 4-15-78

TOLERANCES: ± .010

FINISH: 125-27 NPT

APPROVED: *[Signature]*

TITLE: ACTUATOR ASSEMBLY NOSE GEAR

DATE: 26228-3

1 3/16 x 1 3/8 x 3/32
 70A
 Nit 212

2X500?